

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 02.06.2009

Revision: 02.06.2009

1 Identification of substance/preparation and of the company/undertaking:

- **Product details:**
- **Trade name:** **195 Supertac Food Grade Grease H-1 2**
- **Application of the substance / the preparation** Lubricant
- **Supplier/Manufacturer:**
FGS GmbH
Fahrzeug- und AI- Systeme
Weidenäcker 2
D-78355 Hohenfels
Tel.: +49-7557-9288-0
Fax: +49-7557-9288-18
www.fgs-systems.de
- **Email competent person:** sonja.fischer@kft.de
- **Information department:** See supplier/manufacturer
- **Emergency information:** National Poisons Information Centre Tel.: +44 (0)870 6006266

2 Hazards identification

- **Hazard description:**



N Dangerous for the environment

- **Information pertaining to particular dangers for man and environment:**
R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Classification system:**
The classification was made according to the latest editions of the EC-lists, and expanded using company data and specialized literature.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.
- **Dangerous components:**

CAS: 1314-13-2	zinc oxide	< 2.5%
EINECS: 215-222-5	N; R 50/53	
Index number: 030-013-00-7		
- **Additional information** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **General information:** If symptoms persist or in case of doubt seek medical advice.
- **After inhalation:**
In case of complaints possibly caused by vapours provide fresh air.
If symptoms persist consult a doctor.
- **After skin contact:**
Remove soiled clothes and shoes.
Wash with water and soap and rinse with plenty of water.
If skin irritation continues, consult a doctor.
Immediately seek medical attention if the grease is injected under the skin.
- **After eye contact:** Rinse the eyes with open eyelids for 10 - 15 minutes with water. Then consult an eye specialist immediately.

(Contd. on page 2)
GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 02.06.2009

Revision: 02.06.2009

Trade name: 195 Supertac Food Grade Grease H-1 2

(Contd. of page 1)

- **After swallowing:**
 Drink 3-4 glass of milk or water.
 Call for a doctor immediately.
 Do not induce vomiting.
 If vomiting occurs spontaneously:
 Hold the head of the casualty low with the body in a prone position in order to avoid aspiration.
 Never give anything by mouth to a unconscious person.
 - **Information for doctor:**
 - **The following symptoms may occur:**
 After swallowing:
 Vomiting
 Diarrhoea
 After inhalation:
 irritant effect on the respiratory tract
 - **Treatment:** Symptomatic treatment
-

5 Fire fighting measures

- **Suitable extinguishing agents:**
 Use fire fighting measures that suit the environment.
 Carbon dioxide (CO₂)
 Foam
 Sand
 Water haze
 - **For safety reasons unsuitable extinguishing agents:** Direct jet water
 - **Special hazards caused by the material, its products of combustion or resulting gases:**
 In case of fire formation of dense black smoke
 Dangerous decomposition product see chapter 10: stability and reactivity
 - **Protective equipment:** Wear self-contained respiratory protective device.
 - **Additional information:**
 Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
 Collect contaminated fire fighting water separately. It must not enter the sewage system.
 Cool endangered receptacles with water spray.
-

6 Accidental release measures

- **Person-related safety precautions:**
 Remove persons from danger area.
 Particular danger of slipping on leaked/spilled product.
 Avoid contact with eyes and skin.
 - **Measures for environmental protection:**
 Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to penetrate the ground/soil.
 In case of seepage into the ground inform responsible authorities.
 - **Measures for cleaning/collecting:**
 Absorb with non-combustible material like sand, soil or diatomite.
 Ensure adequate ventilation.
 Send for recovery or disposal in suitable receptacles.
 Dispose contaminated material as waste according to item 13.
-

— GB —
 (Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 02.06.2009

Revision: 02.06.2009

Trade name: **195 Supertac Food Grade Grease H-1 2**

(Contd. of page 2)

7 Handling and storage

- **Handling**
- **Information for safe handling:**
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Avoid inhalation of vapours formed by heated product.
 - Avoid the formation of oil haze.
 - Keep away from heat and direct sunlight.
- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

- **Storage**
- **Requirements to be met by storerooms and receptacles:**
 - Store container tightly sealed at a cool and dry place with sufficient ventilation.
 - Store only in unopened original receptacles.
 - Prevent any seepage into the ground.
- **Information about storage in one common storage facility:**
 - do not store with strong oxidizers
 - Store away from foodstuffs.
 - Store away from feed.
- **Further information about storage conditions:** defend from heat
- **Recommended storage temperature:** < 50°C
- **Storage class** 10 Combustible liquids

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**
 - 1314-13-2 zinc oxide**
 - OEL (Ireland) Short-term value: 10 mg/m³
 - Long-term value: 5 mg/m³
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment**
- **General protective and hygienic measures:**
 - The usual precautionary measures should be adhered to when handling chemicals.
 - Do not inhale gases / fumes / aerosols.
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove soiled soaked clothing and use again only after washing.
 - Wash hands before breaks and at the end of work.
- **Breathing equipment:**
 - Not necessary, if you follow the instructions for use.
 - If vapors are formed use suitable respiratory protective device



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device:
Filter A

- **Protection of hands:**
 - Oil resistant gloves

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 02.06.2009

Revision: 02.06.2009

Trade name: 195 Supertac Food Grade Grease H-1 2

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves:**

Neoprene

Nitrile rubber, NBR

The selection of suitable depends upon the material, and also upon the quality of the gloves. The degree of protection will vary from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:**

The exact penetration time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Tightly sealed goggles.

- **Body protection:**

According to hazard:

Protective work clothing.

Apron

9 Physical and chemical properties:

- **General Information**

Form:	Highly viscous
Colour:	Opaque White Yellowish
Odour:	Weak, characteristic

- **Change in condition:**

Melting point/Melting range: not determined

Boiling point/Boiling range: 315.5°C

- **Flash point:** 226.67°C (C.O.C (ASTM D-92))

- **Self ignition temperature:** Product is not self-igniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Density:** 0.89 g/cm³

- **Solubility in / Miscibility with**

Water: Insoluble

- **pH-value:** not applicable

- **Viscosity:**

kinematic at 40°C: 581 mm²/s

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**

To avoid thermal decomposition do not overheat.

Conditions to be avoided: see chapter 7

- **Materials to be avoided:** Strong oxidants

- **Dangerous reactions:** No dangerous reactions known

- **Dangerous products of decomposition:**

In the case of fire or at high temperatures the formation of the following decomposition products is possible.

Carbon monoxide

unidentified hydrocarbons

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 02.06.2009

Revision: 02.06.2009

Trade name: **195 Supertac Food Grade Grease H-1 2**

(Contd. of page 4)


11 Toxicological information

- **Acute toxicity:**
 - **LD/LC50 values that are relevant for classification:**
- 1314-13-2 zinc oxide**
- Oral LD >8437 mg/kg (rat)
 LDLo 500 mg/kg (men)
 LD₅₀ >5000 mg/kg (rat)
 LD₅₀ (ipr) 240 mg/kg (rat)
- **Primary irritant effect:**
 - **on the skin:**
Continuing or repeated contact with the skin may cause dermatitis.
If injected under the skin, necrosis could result.
 - **on the eye:** Prolonged or repeated contact with the product may cause irritation and reddening.
 - **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Ecotoxicological effects:**
 - **Aquatic toxicity:**
For this preparation are no toxicological data available.
- 1314-13-2 zinc oxide**
- EC₅₀/72h < 1 mg/l (selenastrum capricornutum)
 LC₅₀/96h >320 ppm (Iepomis macrochirus)
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
According to appendix 4 of VwVwS dated 27.7.2005 (German regulation)
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

- **Product:**
 - **Recommendation:**
- 

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal according to instructions of local authorities.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 9 (M6) Miscellaneous dangerous substances and articles.
- **Danger code (Kemler):** 90
- **UN-Number:** 3082

(Contd. on page 6)
GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 02.06.2009

Revision: 02.06.2009

Trade name: 195 Supertac Food Grade Grease H-1 2

(Contd. of page 5)

- **Packaging group:** III
- **Label:** 9
- **Description of goods:** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)
- **Limited quantities (LQ)** LQ7
- **Transport category** 3
- **Tunnel restriction code** E
- **Remarks:** Limited quantity: 5l per inner packaging, 30 kg gross per packaging unit
- **Maritime transport IMDG:**



- **IMDG Class:** 9
- **UN Number:** 3082
- **Label:** 9
- **Packaging group:** III
- **EMS Number:** F-A,S-F
- **Marine pollutant:** No
- **Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 9
 - **UN/ID Number:** 3082
 - **Label:** 9
 - **Packaging group:** III
 - **Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)
 - **Remarks:**
 - Packing Instructions:
 - For Limited Quantities: Y914 (Max Net Qty/Pkg: 30 kg G)
 - Passenger and Cargo Aircraft: 914 /(Max Net Qty/Pkg: 450 l)
 - Cargo Aircraft only: 914 (Max Net Qty/Pkg: 450 l)
 - **Transport/Additional information:** Protect from heat!
-

15 Regulatory information:

- **Markings according to EC guidelines:** The product has been classified according to EC-directives.
- **Code letter and hazard designation of product:**



N Dangerous for the environment

- **Risk phrases:**
 - 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Safety phrases:**
 - 57 Use appropriate container to avoid environmental contamination.
 - 60 This material and its container must be disposed of as hazardous waste.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date: 02.06.2009

Revision: 02.06.2009

Trade name: 195 Supertac Food Grade Grease H-1 2

(Contd. of page 6)

- **National regulations**
 - **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
-

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases:**
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - **Department issuing MSDS:**
KFT Chemieservice GmbH
Marienstr. 3 D-64347 Griesheim
Postfach 1451 D-64345 Griesheim
Tel.: +49-6155-823241
Fax: +49-6155-823246
 - **Contact:** Dr. Sonja Fischer
 - **Sources:** MSDS of the supplier
-