

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 26.05.2009

Revision: 26.05.2009

1 Identification of substance/preparation and of the company/undertaking:

- **Product details:**
- **Trade name: 200S Silver Streak® Special Multi Lube Light**
- **Application of the substance / the preparation** Lubricant
- **Supplier/Manufacturer:**
FGS GmbH
Fahrzeug- und AI- Systeme
Weidenäcker 2
D-78355 Hohenfels
Tel.: +49-7557-9288-0
Fax: +49-7557-9288-18
www.fgs-systems.de
- **Email competent person:** sonja.fischer@kft.de
- **Information department:** See supplier/manufacturer
- **Emergency information:** National Poisons Information Centre Tel.: +44 (0)870 6006266

2 Hazards identification

- **Hazard description:** not applicable
- **Information pertaining to particular dangers for man and environment:**
The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification was made according to the latest editions of the EC-lists, and expanded using company data and specialized literature.
- **Additional information:** DMSO-content <3%

3 Composition/information on ingredients

- **Chemical characterization**
 - **Description:** Mixture of the substances listed below with nonhazardous additions.
 - **Dangerous components:**
- | | | |
|----------------------------|--------------|---------|
| CAS: 1333-86-4 | Carbon black | 2.5-10% |
| EINECS: 215-609-9 | | |
| CAS: 7429-90-5 | aluminium | 2.5-10% |
| EINECS: 231-072-3 | F; R 11-15 | |
| Index number: 013-002-00-1 | | |
- **Additional information** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **General information:** If symptoms persist or in case of doubt seek medical advice.
- **After inhalation:** In case of complaints possibly caused by vapours provide fresh air.
- **After skin contact:**
Remove soiled clothes and shoes.
Wash with water and soap and rinse with plenty of water.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse the eyes with open eyelids for 10 - 15 minutes with water. Then consult a doctor or better an eye specialist.
- **After swallowing:**
Drink 3-4 glass of milk or water.
Call a doctor immediately.

(Contd. on page 2)
— GB —

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 26.05.2009

Revision: 26.05.2009

Trade name: 200S Silver Streak® Special Multi Lube Light

(Contd. of page 1)

- Do not induce vomiting.
 - If vomiting occurs spontaneously:
Hold the head of the casualty low with the body in a prone position in order to avoid aspiration.
Never give anything by mouth to a unconscious person.
 - **Information for doctor:** After swallowing tackiness agents may possibly be coagulated by stomach acids.
 - **The following symptoms may occur:**
 - After swallowing:
Gastric or intestinal disorders.
Diarrhoea
 - After inhalation of high concentrations:
irritant effect on the respiratory tract
 - **Treatment:** Symptomatic treatment
-

5 Fire fighting measures

- **Suitable extinguishing agents:**
Use fire fighting measures that suit the environment.
Carbon dioxide (CO₂)
Foam
Sand
Water haze
 - **For safety reasons unsuitable extinguishing agents:** Direct jet water
 - **Special hazards caused by the material, its products of combustion or resulting gases:**
In case of fire formation of dense black smoke
Dangerous decomposition product see chapter 10: stability and reactivity
 - **Protective equipment:** Wear self-contained respiratory protective device.
 - **Additional information:**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
-

6 Accidental release measures

- **Person-related safety precautions:**
Wear protective clothing.
Particular danger of slipping on leaked/spilled product.
Avid contact with eyes and skin.
 - **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to penetrate the ground/soil.
In case of seepage into the ground inform responsible authorities.
 - **Measures for cleaning/collecting:**
Absorb with non-combustible material like sand, soil or diatomite.
Ensure adequate ventilation.
Send for recovery or disposal in suitable receptacles.
Dispose contaminated material as waste according to item 13.
-

7 Handling and storage

- **Handling**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid inhalation of vapours formed by heated product.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 26.05.2009

Revision: 26.05.2009

Trade name: 200S Silver Streak® Special Multi Lube Light

(Contd. of page 2)

Keep away from heat and direct sunlight.

- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store container tightly sealed at a cool and dry place with sufficient ventilation.

Store only in unopened original receptacles.

- **Information about storage in one common storage facility:**

do not store with strong oxidizers

Store away from reducing agents.

Store away from foodstuffs.

Store away from feed.

- **Further information about storage conditions:** defend from heat

- **Storage class** 10 Combustible liquids

8 Exposure controls and personal protection

- **Additional information about design of technical systems:**

Install appropriate mechanical ventilation.

No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

1333-86-4 Carbon black

WEL (Great Britain) Short-term value: 7 mg/m³Long-term value: 3.5 mg/m³OEL (Ireland) Short-term value: 7 mg/m³Long-term value: 3.5 mg/m³

7429-90-5 aluminium

WEL (Great Britain) Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

OEL (Ireland) Long-term value: 10* 4** ppm

*inhalable **respirable dust

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment**

- **General protective and hygienic measures:**

The usual precautionary measures should be adhered to when handling chemicals.

Immediately remove soiled soaked clothing and use again only after washing.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- **Breathing equipment:**

Not necessary, if you follow the instructions for use.



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device:

Filter A

- **Protection of hands:**

Oil resistant gloves

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 26.05.2009

Revision: 26.05.2009

Trade name: 200S Silver Streak® Special Multi Lube Light

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves:**

Neoprene

The selection of suitable depends upon the material, and also upon the quality of the gloves. The degree of protection will vary from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:**

The exact penetration time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Safety glasses

- **Body protection:**

According to hazard:

Protective work clothing.

Apron

9 Physical and chemical properties:

- **General Information**

Form:	viscous liquid
Colour:	black grey
Odour:	Petroleum-like

- **Change in condition:**

Melting point/Melting range: not determined

Boiling point/Boiling range: 315.5°C

- **Flash point:** 273.89-298.98°C (C.O.C (ASTM D-92))

- **Self ignition temperature:** Product is not self-igniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Density:** 1.08 g/cm³

- **Solubility in / Miscibility with**

Water: Insoluble

- **pH-value:** not applicable

- **Viscosity:**

dynamic: high-viscosity

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**

To avoid thermal decomposition do not overheat.

No decomposition if used and stored according to specifications.

Conditions to be avoided: see chapter 7

- **Materials to be avoided:**

Oxidants

Reducing agents

- **Dangerous reactions:** No dangerous reactions known

- **Dangerous products of decomposition:**

In the case of fire or at high temperatures the formation of the following decomposition products is possible.

fume

Carbon monoxide and carbon dioxide

Sulphur oxides (SO_x)

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 26.05.2009

Revision: 26.05.2009

Trade name: 200S Silver Streak® Special Multi Lube Light

(Contd. of page 4)

 other decomposition products, in the case of incomplete combustion.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-16-1 Petroleum resins
Oral LD₅₀ 7000 mg/kg (mammalian)
64742-58-1 Lubricating oils (petroleum), hydrotreated spent
Oral LD₅₀ >2000 mg/kg (rat)Dermal LD₅₀ >2000 mg/kg (rat)
1333-86-4 Carbon black
Oral LD₅₀ 10000 mg/kg (rat)
68953-58-2 Bentone 34
Oral LD₅₀ >8000 mg/kg (rat)
71011-25-1 Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides, compds. with bentonite and bis(hydrogenated tallow alkyl)dimethylammonium chlorides
Oral LD₅₀ > 5000 mg/kg (rat)Inhalative LC₅₀/1 h > 200 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** Continuing or repeated contact with the skin may cause dermatitis.

- **on the eye:** Slightly irritating

- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Ecotoxic effects:**

- **Aquatic toxicity:**

64742-58-1 Lubricating oils (petroleum), hydrotreated spent
EC₅₀/48h >22500 mg/l (Artemia salina)LC₅₀/48h 2.3-2.5 mg/l (daphnia magna)LC₅₀/96h 74 mg/l (Jordanella floridae)

3.2 mg/l (Pimephales promelas)

64742-62-7 Residual oils (petroleum), solvent-dewaxed
EC₅₀/48h >1000 mg/l (daphnia magna)LC₅₀/96h >5000 mg/l (Onchorhynchus mykiss)

>1000 mg/l (Salmo gairdneri)

71011-25-1 Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides, compds. with bentonite and bis(hydrogenated tallow alkyl)dimethylammonium chlorides
E.C₅₀ > 100 mg/l (selenastrum capricornutum)LC₅₀/96h > 100 mg/l (rainbow trout)

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

According to appendix 4 of VwVwS dated 27.7.2005 (German regulation)

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date: 26.05.2009

Revision: 26.05.2009

Trade name: **200S Silver Streak® Special Multi Lube Light**

(Contd. of page 5)

13 Disposal considerations

- **Product:**
- **Recommendation:**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal according to instructions of local authorities.

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**
- **ADR/RID class:** -
No hazardous good according to the regulation.
- **Maritime transport IMDG:**
- **IMDG Class:** -
No hazardous good according to the regulation.
- **Marine pollutant:** No
- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** -
No hazardous good according to the regulation.

15 Regulatory information:

- **Markings according to EC guidelines:** Observe the general safety regulations when handling chemicals
- **National regulations**
- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases:**
11 Highly flammable.
15 Contact with water liberates extremely flammable gases.
- **Department issuing MSDS:**
KFT Chemieservice GmbH
Marienstr. 3 D-64347 Griesheim
Postfach 1451 D-64345 Griesheim
Tel.: +49-6155-823241
Fax: +49-6155-823246
- **Contact:** Dr. Sonja Fischer
- **Sources:**
MSDS of the supplier
OECD Screening Information Data Sets (SIDS)
National Institute of Technology and Evaluation (Japan)